

MAXIMUM TRAILER WEIGHTS IN POUNDS FOR PROPERLY EQUIPPED VEHICLES WITH NO CARGO



F-150 Lariat SuperCrew® 4x4 in Rapid Red

● GOOSENECK	37,000	Super Duty® Pickup
	34,500	Super Duty Chassis Cab
● 5TH-WHEEL	32,500	Super Duty Pickup
	32,500	Super Duty Chassis Cab
	14,000	F-150 Pickup
● CONVENTIONAL	24,200	Super Duty Pickup
	18,500	Super Duty Chassis Cab
	14,000	F-150 Pickup
	9,300	Expedition
	7,500	Transit Cutaway/Chassis Cab
	7,500	Ranger
	6,900	Transit Cargo Van
	6,500	Transit Crew Van
	5,600	Explorer
	4,600	Transit Passenger Van
	3,500	Bronco
	3,500	Escape
	3,500	Edge
	2,200	Bronco Sport
	2,000	Transit Connect
	2,000	EcoSport
	1,000	Mustang

CUV/SUV/TRUCK TOWING EQUIPMENT & TRAILER TOWING PACKAGES

Model (Option Code)	Transit Connect Van/Wagon (53T)	Bronco Sport (53B)	Escape ¹ (536)	Edge (53G) ²	Explorer (52T)	Expedition (536)	Transit (53B) ¹³	Bronco (53Q) ¹⁴	Ranger (53R)	F-150 Raptor (17T)	F-150 (17T)	F-150 (53B)	F-150 (53A)	F-150 (53C)	F-250/ F-350/F-450 Super Duty Pickup (Std.)	F-250 Super Duty Pickup ⁹ (535)	F-250 Super Duty Pickup ⁹ (53Q)	F-350/F-450/ F-550/F-600 Super Duty Chassis Cab (Std.)	F-350/ F-450/F-550 Super Duty Chassis Cab (531) ¹⁰	F-450/F-550 Super Duty Chassis Cab (535) ⁹
7-Wire Harness & 4-/7-Pin Connector	-	-	-	-	X	S	X ⁴	X	X	-	S	-	X	X	X	S	S	-	-	-
7-Wire Harness (Blunt Cut) with Relays	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X	S	S
Trailer Wiring Harness (4-Pin)	X	X	X	X	-	-	-	-	S	X	-	-	-	-	-	-	-	-	-	-
Trailer Module	X	-	-	-	-	-	-	-	-	S	-	-	-	-	-	-	-	-	-	-
Trailer Wiring Provision	-	-	-	-	-	-	X	-	-	-	-	-	-	-	-	-	-	-	-	-
Hitch Receiver (See chart on page 41)	X	X	X	X	X	S	X	X	X	-	S	-	X	X	X	S	S	-	-	-
Aux. Auto Trans. Oil Cooler	-	-	X	-	-	-	-	-	-	S	-	-	-	-	-	-	-	-	-	-
Radiator Upgrade	-	-	-	-	-	X	-	-	-	S	-	-	-	-	-	-	-	-	-	-
Smart Trailer Tow Connector	-	-	-	-	-	-	-	-	-	S	X	X	X	X	X ⁷	-	-	-	-	-
Trailer Brake Wiring/Feed Kit	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X ⁸	S	S	-	X	X ⁹
Upgraded Rear Axle	-	-	-	-	-	X	-	-	-	S	-	-	-	X	X ⁷	X	X	-	-	X
Increased GCW (6.7L)	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X ⁷	X	X	-	-	X
Upgraded Rear Bumper	-	-	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-	-	-	-
Tow/Haul Mode	-	-	-	-	S	S	X	-	X	X	S	S	S	S	X	S	S	X	S	S
2-Speed Automatic 4WD	-	-	-	-	-	X ³	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Ultimate Trailer Tow Camera System	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	X	-	-	-
Trailer Brake Controller	-	-	-	-	-	X	-	-	-	X	X	-	X	X	X ⁷	S ¹⁰	S ¹⁰	-	-	-
Trailer Sway Control	X	X	X	X	X	S	-	S	S	X	S	S	S	S	X	S	S	X	S	S
Trailer Reverse Guidance	-	-	-	-	-	-	-	-	-	X	X	-	-	-	-	-	-	-	-	-
360-Degree Camera	-	-	-	-	-	-	-	-	-	X	X	-	-	-	-	-	-	-	-	-
Lane Keeping Alert	-	-	-	-	-	-	-	-	-	S	-	-	-	-	-	-	X	-	-	-
Tailgate LED	-	-	-	-	-	-	-	-	-	S	X	-	X	X	-	-	-	-	-	-
Pro Trailer Backup Assist	-	-	-	-	-	X	-	-	-	X	X	-	X ⁵	X ⁵	-	-	X	-	-	-
36-Gallon Fuel Tank	-	-	-	-	-	-	-	-	-	S	-	-	-	X ⁶	-	-	-	-	-	-
Full-Size Spare Tire	-	X	-	-	-	S	S	S	S	X	S	S	S	S	X	S	S	X	S	S

¹ Available with 2.0L EcoBoost® I4 or 2.5L I4 Hybrid/Plug-in Hybrid (SEL or Titanium) only. ² Available with twin-scroll 2.0L EcoBoost I4 only and AWD only. Standard on ST. ³ 4x4 only. ⁴ Includes relay system for backup/B+/running lights. ⁵ Not included on XL 100A. ⁶ Not available with 3.0L Power Stroke® or 3.5L PowerBoost™ engines. ⁷ F-350 DRW/F-450 only. ⁸ In-cab, no controller (SRW). ⁹ Requires 6.7L diesel engine. ¹⁰ Required on XL. ¹¹ XL model only. ¹² Not included if Trailer Brake Controller is ordered. ¹³ Not available on Cutaway or Chassis Cab models. ¹⁴ 53Q featured content is exclusively a factory-installed package.

Notes: • Content may vary depending on model, trim and/or powertrain. See your Ford Dealer for specific content information for all light trucks that will be used for towing to help ensure easy, proper connection of trailer lights.

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. See label on door jamb for carrying capacity of a specific vehicle. For additional information, see your Ford Dealer.

F-150

F-150 King Ranch® SuperCrew 4x2 in Agate Black

CONVENTIONAL TOWING

MAXIMUM LOADED TRAILER WEIGHT (lbs.)

Towing capability will be reduced based on trim series, option content and payload. Prior to making final vehicle selection, reference the Towing Basics information on the last page of this Towing Guide. See dealer and reference "eSourceBook" Job Aid "Spec'ing F-Series Trucks for Towing".

Automatic Transmission			REGULAR CAB				SUPERCAB				SUPERCREW®			
Engine	Axle Ratio	GCWR (lbs.)	4x2		4x4		4x2		4x4		4x2		4x4	
			122.8" WB	141.5" WB	122.8" WB	141.5" WB	145.4" WB	164.1" WB	145.4" WB	164.1" WB	145.4" WB	157.2" WB	145.4" WB	157.2" WB
2.7L GTDI V6 ⁴	3.15	12,200	7,600	—	—	—	—	—	—	—	—	—	—	—
		12,300	—	7,600	—	—	—	—	—	—	—	—	—	—
		12,600	—	—	—	—	7,700	7,600	—	—	—	—	—	—
		12,700	—	—	—	—	—	—	—	—	7,700	—	—	—
		12,800	—	—	—	—	—	—	—	—	—	7,800	—	—
	3.55	12,200	7,600	—	—	—	—	—	—	—	—	—	—	—
		12,300	—	7,600	—	—	—	—	—	—	—	—	—	—
		12,500	—	—	7,700	—	—	—	—	—	—	—	—	—
		12,600	—	—	—	7,700	7,700	7,600	—	—	—	—	—	—
		12,700	—	—	—	—	—	—	—	—	7,700	—	—	—
	3.73	12,800	—	—	—	—	—	—	7,600	—	—	7,800	—	—
		12,900	—	—	—	—	—	—	—	—	—	—	7,700	—
		13,200	8,600	—	—	—	—	—	—	—	—	—	—	—
		13,300	—	8,600	8,500	8,400	8,400	8,300	8,100	—	8,300	8,300	8,100	—
		14,800 ¹	—	10,000	—	—	—	—	—	—	—	—	—	—
3.5L GTDI V6 ⁵	3.31	16,100	—	11,200	—	—	—	—	—	—	—	—	—	—
		16,200	—	—	—	—	11,000	—	—	—	—	—	—	—
		16,400	—	—	—	11,200	—	—	—	—	—	—	—	—
		16,500	—	—	—	—	—	11,200	11,100	—	11,200	—	—	—
		16,600	—	—	—	—	—	—	—	—	—	11,300	—	—
	3.55	16,800	—	—	—	—	—	—	—	11,200	—	—	11,300	11,200
		16,100	—	11,200	—	—	—	—	—	—	—	—	—	—
		16,200	—	—	—	—	11,000	—	—	—	—	—	—	—
		16,400	—	—	—	11,200	—	—	—	—	—	—	—	—
		16,500	—	—	—	—	—	11,200	11,100	—	11,200	—	—	—
	3.73	16,600	—	—	—	—	—	—	—	—	—	11,300	—	—
		16,800	—	—	—	—	—	—	—	11,200	—	—	11,300	11,200
		17,500 ²	—	—	—	—	12,300	—	—	—	—	—	—	—
		17,700 ²	—	—	—	—	—	—	12,300	—	—	—	—	—
		17,900 ²	—	13,000	—	12,700	—	—	—	—	—	—	—	—
	3.73	19,300 ²	—	—	—	—	—	—	—	—	14,000	—	—	—
		19,400 ²	—	—	—	—	—	14,000	—	13,800	—	14,000	13,900	13,800
		18,400 ^{2,3}	—	13,300	—	13,100	—	—	—	—	—	—	—	—
		19,400 ^{2,3}	—	—	—	—	—	14,000	—	13,800	—	14,000	—	—
		19,500 ^{2,3}	—	—	—	—	—	—	—	—	—	—	—	13,800
3.5L GTDI V6 H.O. ⁶	4.10	14,500	—	—	—	—	—	—	—	—	—	—	8,200	—
		14,575 ⁷	—	—	—	—	—	—	—	—	—	—	8,200	—
3.5L Hybrid V6 ⁵	3.55	16,700	—	—	—	—	—	—	—	—	11,000	—	—	—
		16,800	—	—	—	—	—	—	—	—	—	11,100	—	—
	3.73	18,400 ²	—	—	—	—	—	—	—	—	12,700	12,700	—	—
		17,000	—	—	—	—	—	—	—	—	—	—	11,000	11,000
		18,400 ²	—	—	—	—	—	—	—	—	—	—	12,400	12,400

1 Requires 2.7L EcoBoost® Payload Package (622). 2 Requires Max Trailer Tow Package (53C). 3 Requires Heavy-Duty Payload Package (627). 4 Do not exceed a trailer weight of 6,000 lbs. with only the Class IV hitch (53B), without the Trailer Tow Package (53A). 5 Do not exceed a trailer weight of 7,000 lbs. with only the Class IV hitch (53B), without the Trailer Tow Package (53A). 6 Raptor only. 7 Available Raptor 37 Performance Package (68R).

Notes:

- Calculated with SAE J2807® method.
- Do not exceed trailer weight of 5,000 lbs. when towing with bumper only.
- Combined weight of vehicle and trailer cannot exceed listed GCWR.
- Do not exceed the Maximum Loaded Trailer Weight listed.
- Trailer tongue load weight should be 10% of total loaded trailer weight. **Make sure vehicle payload (reduce by option weight) will accommodate trailer tongue load weight and weight of passengers and cargo added to towing vehicle.** Addition of trailer tongue load weight and weight of passengers and cargo cannot cause vehicle weights to exceed rear GAWR or GVWR. These ratings can be found on the vehicle Safety Compliance Certification Label.

Maximum towing capabilities are for properly equipped vehicles with required equipment and a 150-lb. driver and passenger and vary based on cargo, vehicle configuration, accessories, option content and number of passengers. See label on door jamb for carrying capacity of a specific vehicle. For additional information, see your Ford Dealer.

REVISED 05.28.21